H_2SO_4 25 SULFURIC ACID METER H_2SO_4-55

〈Range : 0~200g/ℓ〉

Measurement of H_2SO_4 Density for Plating & Etching Process Liquid

This Meter directly measures high Density Sulfuric Acid out of Etching Liquid etc.
Complicated Dilution or Calculation is not necessary.
Sulfuric acid Density Meter of Simple Operation.
Measuring Object is not Sulfuric Ion but Sulfuric Acid Density.



1 : Possible to measure Sulfuric Acid Density by 0 ~ 199g/ℓ

2 : Colorimeric Measurement of high Density H_2SO_4 within 1 min.

3 : Simple Operation by just Single Reagent

◆Specifications

Product Name	Sulfuric Acid Meter
Model	H_2SO_4-55
Measuring Method	Light Absorbance Method
Measuring Range	0.0~199.9g/ℓ(H_2SO_4)
Display	LCD 3·1/2 digits
Power Supply	Alkaline battery LR03×4(DC 6V)
Outer Dimensions	Approx 88(W)×174(D)×65(H)mm
Weight	Approx 310g
Standard Components	Instrument(H_2SO_4-55), Measuring cell(4pcs), Reagent : H_2SO_4-RA 500mℓ(50 tests),Carrying Case, Micro-Pipette 0.1mℓ
Optional Accessories	Macro-Pipette 10mℓ

Cu 26 COPPER METER $CuSO_4$-55

〈Range : 0~120g/ℓ Cu〉

Measurement of Copper Sulfate for Plating & Etching Process Liquid

This Meter directly measures high Density Copper (Cu) out of Etching Liquid etc.
Complicated Dilution or Calculation is not necessary.
Copper Density Meter of Simple Operation.
Not-Dissolved Copper Can not be measured.



1 : Possible to measure Cu Density by 0 ~ 120g/ℓ

2 : Colorimeric measurement of high Density Cu within 1 min.

3 : Simple Operation by just Single Reagent

◆Specifications

Product Name/Model	Copper Meter
Model	$CuSO_4$-55
Measuring Method	Light Absorbance Method
Measuring Range	0.0~120.0g/ℓ(Copper sulfate density)
Resolution	0.1g/ℓ(0.01%)
Power Supply	Alkaline battery LR03×4(DC 6V)
Outer Dimensions	Approx 88(W)×174(D)×65(H)mm
Weight	Approx 310g
Standard Components	Instrument($CuSO_4$-55), Measuring cell(4pcs), Reagent : $CuSO_4$-RA 500mℓ(50 tests),Carrying Case, Micro-Pipette 0.1mℓ
Optional Accessories	Macro-Pipette 10mℓ